

PRODUCT-DETAILS

# XT1C 160 TMD 40-450 3p F F

# XT1C 160 TMD 40-450 3p F F



## General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | XT1C 160 TMD 40-450 3p F F  |
| Product ID            | 1SDA067393R1  |
| EAN                   | 8015644012175   |
| Catalog Description   | XT1C 160 TMD 40-450 3p F F  |
| Long Description      | C.BREAKER TMAX XT1C 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 40-450 A |

## Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644012175 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 76,2 mm  |
| Product Net Height         | 130 mm   |
| Product Net Depth / Length | 70 mm    |
| Product Net Weight         | 1,072 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 128 mm        |
| Package Level 1 Height         | 135 mm        |
| Package Level 1 Depth / Length | 143 mm        |
| Package Level 1 Gross Weight   | 1,12 kg       |
| Package Level 1 EAN            | 8015644012175 |

## Additional Information

|   |   |
|---|---|
| Circuit Breaker Type to be Associated                       | Power Distribution  |
| Current Type  | AC/DC   |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle   |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle  |
| Number of Poles   | 3   |
| Opening Time  | CB with SOR 15 ms<br>CB with UVR 15 ms  |
| Order Multiple  | 1 piece   |
| Power Loss  | at Rated Operating Conditions per Pole 2.6 W  |
| Product Main Type   | SACE Tmax XT  |
| Product Name  | Moulded Case Circuit Breaker  |
| Product Type  | CB  |
| Rated Current ( $I_n$ )                                     | 40 A  |
| Rated Frequency (f)   | 50 / 60 Hz  |
| Rated Voltage ( $U_r$ )                                     | 690 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV  |
| Rated Instantaneous Short-Circuit Current Setting ( $I_i$ ) | 450 A   |
| Rated Insulation Voltage ( $U_i$ )                          | 800 V   |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC  |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 40 kA<br>(230 V AC) 40 kA<br>(240 V AC) 40 kA<br>(380 V AC) 25 kA<br>(415 V AC) 25 kA<br>(440 V AC) 12.5 kA<br>(500 V AC) 9 kA<br>(525 V AC) 8 kA<br>(690 V AC) 4 kA<br>(250 V DC) 2 Poles in Series 25 kA<br>(500 V DC) 3 Poles in Series 25 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 40 kA<br>(230 V AC) 40 kA<br>(240 V AC) 40 kA<br>(380 V AC) 25 kA<br>(415 V AC) 25 kA<br>(440 V AC) 25 kA<br>(500 V AC) 18 kA<br>(525 V AC) 8 kA<br>(690 V AC) 4 kA<br>(250 V DC) 2 Poles in Series 25 kA<br>(500 V DC) 3 Poles in Series 25 kA  |
| Rated Uninterrupted Current ( $I_u$ )                       | 160 A   |
| Release Type  | TM  |
| Setting Range   | 28...40 A   |

|                          |                              |
|--------------------------|------------------------------|
| Standards                | IEC                          |
| Sub-type                 | XT1                          |
| Terminal Connection Type | Fixed Circuit-Breakers Front |
| Version                  | F                            |

### Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210033D0204 |
| Declaration of Conformity - CE    | 9AKK106713A5532 |
| Environmental Information         | 1SDL000190R0001 |
| GL Certificate                    | 1SDL000163R0103 |
| Instructions and Manuals          | 1SDH000719R0001 |
| LR Certificate                    | 1SDL000163R0100 |

### Classifications

|                            |  |
|----------------------------|--|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q  |
| UNSPSC                     | 39120000   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

### Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

