



Product data sheet

Power tools for trade & industry

Charger

GAL 18V-40



The compact 18 V charger

The most important data

Charge current	4 A
Battery charging voltage	14.4 – 18 V

Order number 1 600 A01 9RN

[> More product information](#)

Technical data

Technical data

Battery charging voltage	14.4 – 18 V
Charge current	4 A
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	24/35 min
Charg. time at bat. cap. 3.0 Ah (80%/100%) approx.	36/50 min
Charg. time at bat. cap. 4.0 Ah (80%/100%) approx.	48/65 min
Charg. time at bat. cap. 5.0 Ah (80%/100%) approx.	60/70 min
Charg. time at bat. cap. 6.0 Ah (80%/100%) approx.	72/95 min
Charg. time ProCORE18V 4.0 Ah (80%/100%) approx.	48/65 min
Charg. time ProCORE18V 8.0 Ah (80%/100%) approx.	113/124 min
Charg. time ProCORE18V 12.0 Ah (80%/100%) approx.	162/172 min
Weight	0.55 kg
Packaging dimensions (width x length x height)	140 x 252 x 96 mm



BOSCH

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Compact: Due to its modern design it is very compact
- With 4 A charging current it charges the GBA 18V 4.0 Ah battery up to 80% in only 48 minutes, GBA 18V 2.0 Ah up to 80% in 24 minutes
- Compatible with all batteries of the Bosch Professional 18V System and the AMPShare Alliance

