



Product data sheet



Rotary Hammer with SDS-plus

GBH 2-26 DRE Professional

The fast all-rounder for daily use

The most important data

Rated power input	800 W
Impact energy	2,7 J
Drilling dia. concrete, hammer drill bits	4 – 26 mm

Part number: 0 611 253 703

[> More product information](#)

Technical Data

Battery and power	
Rated power input	800 W
Performance data	
Impact energy	2,7 J
Impact rate at rated speed	0 – 4.000 bpm
Rated speed	0 – 900 rpm
Bit holder	SDS-plus
Size and weight	
Weight	2,8 kg
Length	377 mm
Width	83 mm
Height	210 mm
Drilling range	
Drilling dia. concrete, hammer drill bits	4 – 26 mm
Opt. appl. range concrete, hammer drill bits	8 – 16 mm
Max. drilling diameter masonry, core cutters	68 mm
Max. drilling diameter in steel	13 mm
Max. drilling diameter in wood	30 mm

Noise/vibration information

Hammer drilling in concrete	
Vibration emission value ah	17,5 m/s ²
Uncertainty K	1,5 m/s ²
Chiselling	
Vibration emission value ah	9,5 m/s ²
Uncertainty K	1,5 m/s ²

**Power tools for trade & industry**

Advantages

- Gets the work done quickly due to fast drilling rate and high chiselling performance because of 800 watt powerful motor and 2.7 joules of impact energy
- Reliable and robust with long lifetime due to high-quality components
- Wide range of applications with rotation stop for chiselling work
- Ball grommet for preventing cable breaks
- Rotating brush plate for equal power in forward and reverse rotation
- Overload clutch to protect the user and the machine

