
Product data sheet





Rotary Hammer with SDS plus

GBH 2-20 D



Bosch's compact entry-level tool in the SDS plus rotary hammer category

The most important data

Rated input power	650 W
Impact energy	1.7 J
Drilling dia. concrete, hammer drill bits	4 – 20 mm

Part Number 0 611 25A 460

> More product information

Technical data

Technical data

reciffical data	
Rated input power	650 W
Impact energy	1.7 J
Impact rate at rated speed	0 – 4,200 bpm
Rated speed	0 – 1,300 rpm
Weight	2.3 kg
Tool dimensions (width)	82 mm
Tool dimensions (length)	323 mm
Tool dimensions (height)	210 mm
Tool holder	SDS plus
Packaging dimensions (width x length x height)	360 x 400 x 115 mm
Voltage, electrical	110 V
Drilling dia. concrete, hammer drill bits	4 – 20 mm
Opt. appl. range concrete, hammer drill bits	4 – 10 mm
Drilling diameter in concrete with core cutters	68 mm
Max. drilling diameter masonry, core cutters	68 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

'Total vibration values (Hammer drilling in concrete)'

Vibration emission value ah	13.5 m/s ²
-----------------------------	-----------------------

Uncertainty K	1.5 m/s ²	
'Total vibration values (Chiselling)'		
Vibration emission value ah	9.5 m/s ²	
Uncertainty K	1.5 m/s ²	

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	13.5 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling	
Vibration emission value ah	9.5 m/s ²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Lightweight and compact housing design optimised for overhead drilling
- Durable due to robust design and construction
- Delivers 1.7 J of impact energy









