

Cordless Impact Wrench GDS 18V-1000



Full power, no cord: 1/2" high torque impact wrench with BITURBO Brushless technology

The most important data

Torque, max.	1,000 Nm
Screw diameter	M 10 - M 24
Weight excl. battery	2.9 kg

Part Number 0 601 9J8 370

> More product information

Technical data

Technical data

recinical uala		
Torque adjustment range, min./max., 1st level	0/350 Nm	
Torque adjustment range, min./max., 2nd level	0/700 Nm	
Torque adjustment range, min./max., 3rd level	0/1000 Nm	
No-load speed	0-1,750 rpm	
No-load speed (1st level)	0-800 rpm	
No-load speed (2nd level)	0-1,200 rpm	
No-load speed (3rd level)	0-1,750 rpm	
Torque settings	3	
Weight excl. battery	2.9 kg	
Torque, max.	1,000 Nm	
Impact rate	0-2,600 bpm	
Impact rate (1st level)	0-1,600 bpm	
Impact rate (2nd level)	0-2,400 bpm	
Impact rate (3rd level)	0-2,600 bpm	
Tool holder	1/2'' Square	
Breakaway torque, max.	1,600 Nm	
Charging time (80%/100%) approx.	68/79 min [8.0 Ah]	
'Total vibration values (Tightening screws and nuts of maximum permitted size)'		
Vibration emission value ah	13.5 m/s²	

Uncertainty K	1.5 m/s²
Screw diameter	
Screw diameter	M 10 - M 24

Noise/vibration information

Tightening screws and nuts of maximum permitted size

Vibration emission value ah	13.5 m/s²
Uncertainty K	1.5 m/s²

Product data sheet Power tools for trade & industry



Advantages:

- High power with cordless freedom thanks to ProCORE18V batteries and brushless motor
- Best performance for heavy duties with a tightening torque of 1,000 Nm and a breakaway torque of up to 1,600 Nm
- High versatility and controlled power due to 3-speed/ torque settings

