



# Product data sheet

Power tools for trade &amp; industry

Cordless Multi-Cutter

## GOP 18V-28



The versatile power performer in the Bosch StarlockPlus category

### The most important data

Battery voltage	18 V
No-load rotation	8,000 – 20,000 opm
Oscillation angle on left and right	1.4 °

**Part Number** 0 601 8B6 001[> More product information](#)

## Technical data

### Technical data

Battery voltage	18 V
No-load rotation	8,000 – 20,000 opm
Oscillation angle on left and right	1.4 °
Weight excl. battery	1.2 kg
Packaging dimensions (width x length x height)	360 x 440 x 155 mm
Weight incl. battery	1.6 kg

### 'Total vibration values (Grinding)'

Vibration emission value ah	3.4 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

### 'Total vibration values (Sawing with plunge-cutting saw blade)'

Vibration emission value ah	8 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

### 'Total vibration values (Sawing with segment saw blade)'

Vibration emission value ah	5.7 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

## Noise/vibration information

### Grinding

Vibration emission value ah	3.4 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

### Sawing with plunge-cutting saw blade

Vibration emission value ah	8 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

### Sawing with segment saw blade

Vibration emission value ah	5.7 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

### Scraping

Vibration emission value ah	8.6 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>



# Product data sheet

Power tools for trade & industry

## Advantages:

- Superior Starlock interface of optimised 3-dimensional tight connection for highest direct power transfer
- LED spot illuminates workspaces, improving work visibility even in the dark
- Snap-in function enables fast and easy tool accessory change

