


Material number	0 611 316 703	0 611 316 704	0 611 316 755
EAN	3165140203869	3165140203876	3165140759465
Auxiliary handle 2 602 025 076	✓	✓	✓
Carrying case 2 605 438 297	✓	✓	✓
Flat chisel 400 x 25 mm 1 618 600 202	✓	✓	
Flat chisel RTec Sharp, SDS-max 2 608 690 124			✓
Grease tube SP no. 1 615 430 010	✓	✓	✓
Machine cloth	✓		
Package (L/W/H)	620x415x135 mm		

Technical data

Technical Data

Rated power input	1500 W
Impact energy	25 J
Impact rate at rated speed	900 - 1890 bpm
Weight without cable	10,1 kg
Length	570 mm
Height	270 mm
Toolholder	SDS-max



Functions

Constant Electronic	✓
---------------------	---

Noise/vibration information

Vibration level (drilling/chiselling)	18,5 m/s ²
---------------------------------------	-----------------------

Sales information

Key Message

- The specialist tool for breakthroughs and demolition work

User benefits

- Extreme impact force of 16.8 joules for high material removal rate
- Low-vibration in operation and no-load
- Low feed pressure, for fatigue-free working

Other features

- Wide sliding switch for convenient switching on and off
- Variable chisel fitting in 12 positions
- Auxiliary handle can be adjusted and rotated 360°
- SDS-max toolholder with integrated dust protection
- Large-volume carrying case
- Service display indicates an impending carbon brush change