# 0 611 338 6F0 - GSH 500

Material number	0 611 338 6F0	0 611 338 6K0
EAN	3165140895606	3165140895613
1 x pointed chisel, 17 mm hex shank, 280 mm available separately as set of 10: 2 608 690 350	✓	<b>√</b>
Carrying case	✓	✓
Tool dimensions (length)	458 mm	458 mm




### **Technical data**

### **Technical data**

Rated input power	1.100 W
Impact energy	7.8 J
Impact rate at rated speed	3 bpm
Weight	5,6 kg
Tool dimensions (width)	103 mm
Tool dimensions (length)	458 mm
Tool dimensions (height)	235 mm
Tool holder	17 mm HEX







### Segment

Segments	Hammers Demolition Hammer Concrete
Mailing segment	Stone



## 0 611 338 6F0 - GSH 500

### **Sales information**

### **Positioning**

■ "Fast & Reliable" - The NEW Chipping Specialist!

#### User benefit

- Greater efficiency: High impact energy coupled with higher impact rate resulting in 10% higher chipping output
- Extended durability: Patented grease sealing ring to prevent leakage; improved dust cap for better dust proof with easy chisel fixing/removing
- Less fatigue: Lowest vibration in its class to ensure ease of operation thanks to well designed damping ring system

