

TECHNICAL DATA

Additional data

Battery voltage	12 V
Torque (soft/hard/max.)	14/30/- Nm
No-load speed (1st gear / 2nd gear)	0 – 400 / 0 – 1,500 rpm
Weight excl. battery	0.8 kg
Battery type	Lithium-ion
Chuck capacity, min./max.	0.8 / 10 mm
Torque settings	20+1

Screw diameter

Max. screw diameter	8 mm
---------------------	------

Drilling diameter

Max. drilling diameter in wood	20 mm
Max. drilling diameter in steel	10 mm

Total vibration values (Drilling in metal)

Vibration emission value ah	0.7 m/s ²
Uncertainty K	1.5 m/s ²

Total vibration values (Screwdriving)

Vibration emission value ah	0.4 m/s ²
-----------------------------	----------------------

Total vibration values (Screwdriving)

Uncertainty K	1.5 m/s ²
---------------	----------------------

Noise/vibration information

Sound pressure level	67 dB(A)
----------------------	----------

Sound power level	78 dB(A)
-------------------	----------

Uncertainty K	3 dB
---------------	------

Drilling in metal

Vibration emission value ah	0.7 m/s ²
-----------------------------	----------------------

Uncertainty K	1.5 m/s ²
---------------	----------------------

Screwdriving

Vibration emission value ah	0.4 m/s ²
-----------------------------	----------------------

Uncertainty K	1.5 m/s ²
---------------	----------------------

The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB(A).
Uncertainty K= dB.