





DEWALT D25413K-LX 32MM HEAVY DUTY SDS PLUS COMBINATION HAMMER 110V

MODEL # D25413K-LX

- Active vibration control system incorporating a floating rear handle to reduce vibration
- Ideal for drilling large anchor; fixing and through holes in concrete and masonry from 6 to 32 mm in diameter
- Optimized power to weight ratio good power in a lightweight package

FEATURES:

- Active vibration control system incorporating a floating rear handle to reduce vibration
- Ideal for drilling large anchor; fixing and through holes in concrete and masonry from 6 to 32 mm in diameter
- Optimized power to weight ratio good power in a lightweight package
- Large hammer mechanism construction guarantees longer tool life and superior performance
- Rotation-stop for light chiseling applications; render and tile removal
- Electronic variable speed switch for total control
- Mechanical clutch increases user control and protection
- Impact-stop for drilling in wood; ceramic; steel and screw driving applications

SPECIFICATIONS:

Tool Holder: SDS-Plus

- Power Input: 1000 Watts
- Power Output: 450 Watt
- Impact energy (EPTA 05/2009): 4.2 J
- No Load Speed: 0-820 rpm
- Blows per Minute: 0-4700 bpm
- Max. Drilling Capacity [Concrete]: 32 mm
- Max. Drilling Capacity [Core bit]: 100 mm
- Max. Drilling Capacity [Wood]: 32 mm
- Max. Drilling Capacity [Metal]: 13 mm
- Weight: 4.2 kg
- Length: 370 mm
- Height: 250 mm
- Width: 85 mm
- Hand/Arm Vibration Hammer drilling into concrete: 8.2 m/s²
- Uncertainty K 1 (Vibration): 1.5 m/s²
- Hand/Arm Vibration Chiseling: 7.1 m/s²
- Uncertainty K 2 (Vibration): 1.5 m/s²
- Hand/Arm Vibration Drilling into metal: <2.5 m/s²
- Uncertainty K 3 (Vibration): 1.5 m/s²
- Hand/Arm Vibration Screw driving without impact: <2.5 m/s²
- Uncertainty K 4 (Vibration): 1.5 m/s²
- Sound Pressure: 86 dB(A)
- Sound Pressure Uncertainty: 3.0 dB(A)
- Sound Power: 97 dB(A)
- Sound Power Uncertainty 3 dB(A)

INCLUDED:

- 360° side handle
- Depth rod
- Kit Box
- Instruction Manual