



D25481K-B5

40MM SDS Max Combination Hammer w/
AVC 5Kg 220V

FEATURES

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 40 mm in diameter. Core drilling up to 90 mm
- Chain drive improves durability and increases efficiency together with an oil filled gearbox to ensure total component lubrication and superior heat dissipation
- Ergonomic, compact and slim line design maximizes control and offers easy access to confined spaces
- Excellent power to weight ratio: 8 Joules of impact energy delivered by a 6.1 kg hammer
- Rotation-stop for medium-light demolition applications
- Unique dust sealing protection to prevent even the finest dust ingress into the hammer mechanism delivering high durability and extended tool life
- Hammer mechanism is optimized by reducing the number of components and by improving dampening to deliver maximum impact energy and therefore the efficiency to drill into the hardest concrete
- Efficient mechanism delivers impact blows directly to the bit without losses through excessive vibration and rebound dampening reduces stress to the tool
- Soft rubber grip handles improve user comfort lowering fatigue during extended use

SPECIFICATIONS

Tool Holder	SDS-Max
Power Input	1100 Watts
Power Output	500 Watt
Impact energy (EPTA 05/2009)	8 J
Load Speed	400 rpm
Blows per Minute	2740 bpm

Max. Drilling Capacity [Concrete]	40 mm
Max. Drilling Capacity [Breakthrough bit]	55 mm
Max. Drilling Capacity [Core bit]	90 mm
Weight	6.1 kg
Length	457 mm
Height	245 mm
Width	104 mm
Hand/Arm Vibration - Hammer drilling into concrete	18.3 m/s ²
Uncertainty K 1 (Vibration)	1.8 m/s ²
Hand/Arm Vibration - Chiseling	13.2 m/s ²
Uncertainty K 2 (Vibration)	1.6 m/s ²
Sound Pressure	94 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	104 dB(A)
Sound Power Uncertainty	3 dB(A)