

TECHNICAL DATA

# Fluke BP7235 NiMH Battery Pack



## Key features

7.2V 3500 mA-hour rechargeable Ni-MH battery pack. This item replaces BP7217 Ni-Cd Battery Pack

Includes one battery pack.

## Product overview: Fluke BP7235 NiMH Battery Pack

7.2 V 3500 mA-hour rechargeable Ni-MH battery pack. Provides typical 16-hour battery life when used in 700 or 740 Calibrator.

## Specifications: Fluke BP7235 NiMH Battery Pack

General Specifications	
Material	Six 1.2 V DC Ni-MH cells in custom-molded ABS/PC-blend case
Application	7.1 x 2.2 x .9 in (150 x 56 x 22 mm)
Dimensions	7.1 x 2.2 x .9 in (150 x 56 x 22 mm)
Weight	11 oz / 310g
Warranty	One year

This item replaces BP7217 Ni-Cd Battery Pack.

## Ordering information



### **Fluke BP7235**

NiMH Battery Pack

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Europe B.V.**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com/en](http://www.fluke.com/en)

©2023 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
07/2023

**For more information call:**  
In Middle East/Africa  
+31 (0)40 267 5100

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**