

## TECHNICAL DATA

## Fluke STL120 Shielded Test Leads



### Key features

- Length: 1.2m (48")
- Bandwidth: 12,5 MHz
- Maximum Signal Voltage: 600V rms. CAT III per IEC 1010-2-031
- Maximum Voltage to Ground: 600V rms. CAT III per IEC 1010-2-031
- Maximum Current: 1A

### Product overview: Fluke STL120 Shielded Test Leads

Set of two (one red, one gray) double insulated silicone shielded test leads for noise free measurements. Specially designed for use with the Fluke ScopeMeter 120 Series. Compatible with AC120 Alligator Clips and HC120 Hook Clips. Safety designed ground leads included. Integral strain relieve and extra hard probe tips provide extra long service life. Features safety designed shrouded plugs and notched tip to prevent probe from sliding.

## Ordering information



### **Fluke STL120**

Fluke STL120 Shielded Test Leads

---

Shielded Test Leads

---



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2023 Fluke Corporation.  
Specifications subject to change without notice.  
07/2023

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**