



ESS LV Battery

25.6V-5.12kWh

Product Features

- Class-A LiFePO4 Battery**
6000 Life Cycle
High Safety and Performance
- Solid Quality**
Cells Contact System(CCS) Integrated Design
and Manufacturing Technique
- Intelligent BMS**
50+ Protection Algorithms for Safety
and Longer Lifespan
- Automatic Parallel Address**
Up to 32 Parallel
No Dip Switch, Automatic Set to Parallel Address
Automatic Assign Master and Slave
- High Compatibility**
Self-adaptive Communicate with Mainstream Inverter
Maximum Discharge Power up to 10kW@10S

Model	IPL-25200X
Battery Type	LiFePO4
Nominal Voltage	25.6V
Nominal Energy	5.12kWh
Nominal Capacity	200Ah
Operating Voltage Range	21.6V~28.8V
Standard Charging Current	100A
Maximum Continuous Charge Current	200A
Cut-Off Charging Voltage	28.8V
Cut-Off Charging Current	1A
Standard Discharge Current	100A
Maximum Continuous Discharge Current	200A
Maximum Pulse Discharge Current	220A
Cut-Off Discharge Voltage	21.6V
Cut-Off Discharge Current	1A
Dimensions	240mm*490mm*618mm
Weight	±3 48kg
Communication Port	RS485/CAN/RS232
Parallel Number	32
Working Temperature/Charge	0 C ~+55 C
Working Temperature/Discharge	-20 C ~+60 C
Ingress Protection	IP20
Cooling Type	Natural Cooling
Humidity	10%-95%
Altitude (m)	2000m
Shell Material	Metal
Current Limiting Function	20A
Precharge Function	Enable
Display Mode	LED
Design Life	10 Years
Cycle Life	>6000@25 C ,0.5C,80%DOD
Authentication Level	IEC62619\UN38.3\MSDS\DGM