



On-Grid Inverter  
with Energy Storage

# Krypton 7500



In Built Wifi



Intelligent Load Management



Grid Feeding



Batteryless Operation



Dual Output



Battery management system

Models: Hybrid Infini VIII 6KW-48V



Easy-to-install

- Pure sine wave output
- Self-consumption and Feed-in to the grid
- Built-in MPPT solar charger
- Programmable supply priority for PV, Battery or Grid



Reliable

- User-adjustable charging current and voltage
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup
- Detachable LCD panel



User-friendly

- Built-in WiFi for mobile monitoring (APP is available)
- Supports USB on-the-go function
- Reserve BMS communication
- Parallel operation up to 9 units

<b>MODEL</b>	<b>HYBRID INFINI V III 6KW-48V</b>
Phase	1-phase in / 1-phase out
Maximum PV Input Power	7500 W
Rated Output Power	6000 W
Maximum Charging Power	6000 W
<b>GRID-TIE OPERATION</b>	
<b>PV INPUT (DC)</b>	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	120VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 27A
<b>GRID OUTPUT (AC)</b>	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)
Nominal Output Current	26A
Power Factor	> 0.99
<b>EFFICIENCY</b>	
Maximum Conversion Efficiency (DC/AC)	95%
<b>OFF-GRID OPERATION</b>	
<b>AC INPUT</b>	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Frequency Range	50 Hz/60 Hz (Auto sensing)
Maximum AC Input Current	40 A
<b>PV INPUT (DC)</b>	
Maximum DC Voltage	500 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 27A
<b>BATTERY MODE OUTPUT (AC)</b>	
Nominal Output Voltage	220/230/240 VAC
Output Waveform	Pure sine wave
Efficiency (DC to AC)	93%
<b>HYBRID OPERATION</b>	
<b>PV INPUT (DC)</b>	
Nominal DC Voltage / Maximum DC Voltage	360 VDC / 500 VDC
Start-up Voltage / Initial Feeding Voltage	120VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 430 VDC
Number of MPP Trackers / Maximum Input Current	1 / 27A
<b>GRID OUTPUT (AC)</b>	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)
Nominal Output Current	26A
<b>AC INPUT</b>	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Maximum AC Input Current	40 A
<b>BATTERY MODE OUTPUT (AC)</b>	
Nominal Output Voltage	220/230/240 VAC
Efficiency (DC to AC)	93%
<b>BATTERY &amp; CHARGER</b>	
Nominal DC Voltage	48 VDC
Maximum Solar Charging Current	120 A
Maximum AC Charging Current	120 A
Maximum Charging Current	120 A
<b>GENERAL</b>	
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	140 x 365 x 468
Net Weight (kgs)	14
<b>INTERACE</b>	
Parallel Function	Yes, 9 units
Communication Port	USB, RS-232, Dry Contact and WiFi
<b>ENVIRONMENT</b>	
Humidity	0 ~ 90% RH (No condensing)
Operating Temperature	-10°C to 50°C

