



## Floor Standing



Auto Restart



Quiet Design



LCD Display



Anti-Rust Cabinet



Easy-clean Panel



Valve Protection Cover



Self-diagnosis and Auto-protection



Independent Dehumidification

# Floor Standing

## Specifications: Floor Standing

Model		MFM-48ARN1	MFM-60ARN1
Power supply	V-ph-Hz	380~415-3-50	380~415-3-50
Cooling performance			
Capacity	Btu/h	48000	60000
Input	W	5540	7390
Current	A	9.6	12.8
EER	W/W	2.73	2.61
Heating performance			
Capacity	Btu/h	48000+12000	60000+12000
Input	W	5200+3700	5300+3500
Current	A	9.8+5.8	10.0+5.3
COP	W/W	2.85	3.43
Indoor unit			
Indoor air flow (Hi/Med/Lo)	m <sup>3</sup> /h	1700/1480	2250/1950
Noise level (Hi/Med/Lo) indoor	dB(A)	52/49	54/51
Dimension (WxDxH)	mm	550x418x1824	600x455x1934
Packing (WxDxH)	mm	1935x655x540	2040x745x595
Net/Gross weight	kg	55.8 / 70	68.5 / 86
Outdoor unit			
Outdoor noise level	dB(A)	64	64
Dimension (WxDxH)	mm	900x350x1170	900x350x1170
Packing (WxDxH)	mm	1032x443x1307	1032x443x1307
Net/Gross weight	kg	97 / 107	96 / 107
Refrigerant type/quantity			
Type		R410A/3300g	R410A/3200g
Charged volume	kg	4.2/1.5	4.2/1.5
Refrigerant piping			
Liquid side/Gas side	mm (inch)	Φ12.7/Φ19 (1/2"/3/4")	Φ12.7/Φ19 (1/2"/3/4")
Max. pipe length	m	20	20
Max. difference in level	m	10	10

### Remarks:

1. The above design and specifications are subject to change without prior notice for product improvement.
2. The sound levels in the table above reflect the levels as taken in an anechoic chamber.