

PD-705 | 705 W percussion drill



- Compact and powerful 705 W motor.
- Compact ergonomic design with large soft grip areas offers excellent handling.
- Variable speed control with forward and reverse mechanism.
- Hammer action stop for rotary drilling.
- 13 mm metal keyless chuck.
- 43 mm gear neck diameter for use in drill stands.
- 4 m cable.

	PD-705
Chuck capacity (mm)	13
Max. drilling concrete (mm)	15
Max. drilling masonry (mm)	16
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	0 - 48,000
Max. static stalling torque (Nm)	15
No load speed (rpm)	0 - 3000
Power input (W)	705
Sound power level measured (dB(A))	110,0
Sound power level measured uncertainty (dB(A))	3,0
Sound pressure level (dB(A))	99,0
Sound pressure level uncertainty (dB(A))	3,0
Standard equipment	Chuck, side handle, depth gauge, cable
Vibration drilling into concrete [m/s ²]	12.6
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Vibration drilling into Metal [m/s ²]	5.6
Vibration drilling into metal uncertainty [m/s ²]	1.5
Weight (kg)	1.9