●NF-S (Standard class)

	100			125			125			125		160			225			250		
	NF125-SV						NF125-SGV			NF125-SEV		NF160-SGV			NF250-SV					
	(15) 16 20 (30) 32 40 50 (60) 63 (75) 80 100			125			16-20 20-25 25-32 32-40 35-50 45-63 56-80 70-100 90-125			16-32 32-63 63-125		125-160			(100) 125 150 160 175 200 225 (*2)			250		
	2	3	4	2	3	4	2	3	4	3	4	2	3	4	2	3	4	2	3	4
	690			690			690			690		690			690			690		
	8/8			8/8			8/8			8/8		8/8			8/8			8/8		
	18/18			18/18			30/30			30/30		30/30			30/30			30/30		
	25/25			25/25			36/36			36/36		36/36			36/36			36/36		
	30/30			30/30			36/36			36/36		36/36			36/36			36/36		
	30/30			30/30			36/36			36/36		36/36			36/36			36/36		
	30/30			30/30			36/36			36/36		36/36			36/36			36/36		
	50/50			50/50			85/85			85/85		85/85			85/85			85/85		
	50/50			50/50			85/85			85/85		85/85			85/85			85/85		
	40/40 (*3)			40/40 (*3)			20/20 (300V) (*3)			–		20/20 (300V) (*3)			20/20 (300V) (*3)			20/20 (300V) (*3)		
	8			8			8			8		8			8			8		
	AC/DC compatible			AC/DC compatible			AC/DC compatible			AC		AC/DC compatible			AC/DC compatible (*1)			AC/DC compatible (*1)		
	Compatible			Compatible			Compatible			Compatible		Compatible			Compatible			Compatible		
	Possible			Possible			Possible			Possible		Possible			Possible			Possible		
	25,000			25,000			50,000			25,000		40,000			25,000			25,000		
	10,000			10,000			30,000			10,000		15,000			10,000			10,000		
	A			A			A			A		A			A			A		
	3			3			3			3		3			3			3		
	N/A			N/A			N/A			A		N/A			N/A			N/A		
	60	90	120	60	90	120	105		140	105	140	105		140	105		140	105		140
	130			130			165			165		165			165			165		
	68			68			68			68		68			68			68		
	90			90			92			92		92			92			92		
	0.7	1.0	1.3	0.7	1.0	1.3	1.4	1.6	2.0	1.7	2.2	1.4	1.6	2.0	1.4	1.6	2.0	1.4	1.6	2.0
	●Screw terminal			●Screw terminal			●Screw terminal			●Screw terminal		●Screw terminal			●Screw terminal			●Screw terminal		
	●			●			●			●	●	●			●		●	●		●
	●Bar stud			●Bar stud			●Bar stud			●Bar stud	●Bar stud	●Bar stud			●Bar stud			●Bar stud		
	●		●	●		●	●			●	●	●			●		●	●		●
	● (*4)		●	● (*4)		●	● (*4)		●	● (*4)	●	● (*4)		●	● (*4)		●	● (*4)		●
	● (*4)		●	● (*4)		●	● (*4)		●	● (*4)	●	● (*4)		●	● (*4)		●	● (*4)		●
	● (*4)		●	● (*4)		●	● (*4)		●	● (*4)	●	● (*4)		●	● (*4)		●	● (*4)		●
	● (*4)		●	● (*4)		●	● (*4)		●	● (*4)	●	● (*4)		●	● (*4)		●	● (*4)		●
	●		●	●		●	●			●	●	●			●		●	●		●
	–			–			–			●		–			–			–		
	●		–	●		–	●		–	●	–	●		–	●		–	●		–
	●		–	●		–	●		–	●	–	●		–	●		–	●		–
	–	●	–	–	●	–	●		–	●	–	●		–	●		–	●		–
	–	●		–	●		●			●		●			●			●		
	●		●	●		●	●			●	●	●			●		●	●		●
	●		–	●		–	●			●	–	●			●		–	●		–
	●			●			●			●		●			●			●		
	●			●			●			●		●			●			●		
	●			●			●			●		●			●			●		
	●			●			●			●		●			●			●		
	–	●	●	–	●		●			●		●			●			●		
	●		●	●		●	●			●	●	●			●		●	●		●
	●		●	●		●	●			●	●	●			●		●	●		●
	●		●	●		●	●			●	●	●			●		●	●		●
	–			–			–			–		–			–			–		
	Self-declaration			Self-declaration			Self-declaration			Self-declaration		Self-declaration			TÜV approval		Self-declaration	TÜV approval		Self-declaration
	Recognition in process			Recognition in process			Recognition in process			Recognition in process		Recognition in process			Recognition in process			Recognition in process		
	☆		–	☆		–	☆ (LR, ABS, GL)		–	☆ (LR, ABS, GL)	–	☆ (LR, ABS, GL)		–	☆		–	☆		–
	Thermal-magnetic			Thermal-magnetic			Thermal-magnetic			Electronic (effective value detection)		Thermal-magnetic			Thermal-magnetic			Thermal-magnetic		
	Equipped			Equipped			Equipped			Equipped		Equipped			Equipped			Equipped		
	764			764			772			774		772			768			768		

Remarks: 1. Products with rated current parenthesized are produced when an order is placed.
2. Specify "P-LT" when using a plug-in product with a lead-wire terminal block.
3. The circuit breaker has the rated short-circuit breaking capacity specified in the shaded cells.