●NF-C (Economy class)

	225	250	400	600	630	800
	NF250-CV		NF400-CW	NF630-CW		NF800-CEW
	(100) 125 150 175 200 225 (*3)	250	250 300 350 400	500 600	630	Adjustable 400 450 500 600 700 800
	2 3	2 3	2 3	2 3	2 3	3
	600	600	690	690	690	690
	–	–	–	–	–	–
	10/8	10/8	15/8	18/9	18/9	18/9
	15/12	15/12	25/13	36/18	36/18	36/18
	25/19	25/19	36/18	36/18	36/18	36/18
	25/19	25/19	36/18	36/18	36/18	36/18
	25/19	25/19	40/20	40/20	40/20	40/20
	36/27	36/27	50/25	50/25	50/25	50/25
	36/27	36/27	50/25	50/25	50/25	50/25
	15/12 (*4)	15/12 (*4)	20/10 (*4)	20/10 (*4)	20/10 (*4)	–
	8	8	8	8	8	8
	AC/DC compatible	AC/DC compatible	AC/DC compatible	AC/DC compatible	AC/DC compatible	AC
	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible
	Possible	Possible	Possible	Possible	Possible	Possible
	8,000	8,000	6,000	6,000	6,000	4,000
	4,000	4,000	1,000	1,000	1,000	500
	A	A	A	A	A	B
	3	3	3	3	3	3
	N/A	N/A	N/A	N/A	N/A	A
	105	105	140	140	140	210
	165	165	257	257	257	275
	68	68	103	103	103	103
	92	92	134	134	134	155
	1.3 1.5	1.3 1.5	4.4 5.0	5.2 6.0	5.2 6.0	10.9
	●Screw terminal	●Screw terminal	●Busbar terminal	●Busbar terminal	●Busbar terminal	●Busbar terminal
	●	●	–	–	–	–
	●Bar stud	●Bar stud	●Bar stud	●Bar stud	●Bar stud	●Bar stud
	●	●	●	●	●	●
	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)
	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)
	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)	●(*6)
	●(*6)	●(*6)	●	●	●	●
	●	●	●	●	●	●
	–	–	–	–	–	●(*9)
	●	●	–	–	–	–
	●	●	●	●	●	●
	– ●	– ●	●	●	●	●
	●	●	●(*8)	●(*8)	●(*8)	●(*8)
	●	●	●	●	●	●
	●	●	●	●	●	●
	●	●	–	–	–	–
	●	●	●	●	●	●
	●	●	●	●	●	●
	●	●	●	●	●	●
	●	●	●	●	●	●
	●	●	●	●	●	●
	●	●	● ●	● ●	● ●	●
	●	●	●	● ●	● ●	●
	–	–	–	–	–	–
	TÜV approval	TÜV approval	Self-declaration	Self-declaration	Self-declaration	Self-declaration
	Recognition in process	Recognition in process	Recognition in process	Recognition in process	Recognition in process	Recognition in process
	☆	☆	☆	☆	☆	☆
	Thermal-magnetic	Thermal-magnetic	Thermal-magnetic	Thermal-magnetic	Thermal-magnetic	Electronic (effective value detection)
	Equipped	Equipped	Equipped	Equipped	Equipped	Equipped
	768		776	782		786

Remarks: 1. Products with rated current parenthesized are produced when an order is placed.
2. Specify "P-LT" when using a plug-in product with a lead-wire terminal block.
3. The circuit breaker has the rated short-circuit breaking capacity specified in the shaded cells.