

EKFL15D10L

PIXEL

Cylindrical Fuse Link



General

Rated voltage: 1500V

Rated current: 2A~35A

Core size: 10×85mm

Utilization category: gPV

Standard: IEC60269-6

Breaking capacity: 50kA

Main Technical Data

Model	Rated current (A)	I ² t (Amps ² seconds)		Power loss (W)	
		Pre-arcing	Total clear	0.8In	1.0In
EKFL15D10L02	2	4	8	1.0	2.0
EKFL15D10L03	3	6	11	1.1	2.1
EKFL15D10L04	4	8	14	1.2	2.2
EKFL15D10L05	5	11	22	1.4	2.4
EKFL15D10L06	6	15	30	1.5	2.6
EKFL15D10L08	8	9	35	1.8	3.0
EKFL15D10L10	10	10	98	2.2	3.5
EKFL15D10L12	12	12	120	2.5	3.8
EKFL15D10L15	15	14	170	3.0	4.8
EKFL15D10L20	20	34	400	3.5	6.2
EKFL15D10L25	25	65	550	4.0	7.2
EKFL15D10L30	30	95	750	4.5	8.3
EKFL15D10L32	32	116	792	4.8	8.9
EKFL15D10L35	35	143	980	5.0	9.3

Dimension (mm)

