

RUBIMIX-9 N

Versatility by changing the mixing paddle.
For cementitious adhesives, resins, paints and other materials.

1
Prepare



3+1
YEARS
WARRANTY

W
1200 W

CE | EAC | UK
CA

	REF			W		RPM			
RUBIMIX-9 N	25940		SUPERPRO	1200 W	210-240V 50-60 Hz. 1ª 0-650 / 2ª 0-850	12.1 Lb 5.5 kg	2	24	
RUBIMIX-9 N UK	25942		SUPERPRO	1200 W	110-130V 50-60 Hz. 1ª 0-650 / 2ª 0-850	12.1 Lb 5.5 kg	2	24	
RUBIMIX-9 N UK	25944		SUPERPRO	1200 W	210-240V 50-60 Hz. 1ª 0-650 / 2ª 0-850	12.1 Lb 5.5 kg	2	24	
RUBIMIX-9 N + CHUCK	24986		SUPERPRO	1200 W	210-240V 50-60 Hz. 1ª 0-650 / 2ª 0-850	12.3 Lb 5.6 kg	2	24	
RUBIMIX-9 N USA + CHUCK	24949		SUPERPRO	1200 W	110-130V 50-60 Hz. 1ª 0-650 / 2ª 0-850	12.3 Lb 5.6 kg	2	24	
RUBIMIX-9 N + CASE	24958	✓	SUPERPRO	1200 W	210-240V 50-60 Hz. 1ª 0-650 / 2ª 0-850	17.2 Lb 7.8 kg	2	18	

- Higher mixing performance, thanks to a more efficient torque.
- 2 speed gearbox and progressive switch (R.P.M. regulation) to optimize the mixing of each material.
- Quick and easy to change the brushes. High comfort.
- Safety lock to prevent unexpected start.

- Power: 1200 W.
- Double insulation.
- Direct connection M14 thread.
- Electronic regulator (1st 0-650 r.p.m. / 2nd 0-850 r.p.m.). Ø maximum paddle: 140 mm.
- Ø 4 3/4" (120 mm) mixing paddle included.

Accessories:



Mortar Mixer M14 Thread 3 ZN-Zinc plated HELIX



Plaster mixer paddle Thread M-14



Mortar mixer paddle Thread M14 3 HELIX



RUBIMIX buckets

