

DS-250 N

For wall tiles, floor tiles, porcelain tiles, marble, granite and other materials.



3 cv/hp



2 1/16"
51 mm



mm
inch



- 1 Motor assembly mounted on sliding bearings for maximum precision and reliability. Perfect finishes.
- 2 Equipped with ZERO DUST system. Tested and certified by TNO.
- 3 Wheels and handle included. Easy transport.
- 4 Aluminium structure. Lighter cutter with maximum resistance to working conditions.

- Removable aluminium tables for easy cleaning of the machine.
- With thermic security switch.
- Water pump refrigeration of blade with flow control valve.
- Diamond blade Ø10" (250mm) not included.
- With a double set of flanges, one especially designed for mitre cuts.
- Motor assembly mounted on sliding bearings for maximum accuracy mitre cuts.
- Safety protector for segmented blades.
- With lateral stop for repetitive cuts.
- Retractable legs with "shield" function and wheels for easy transportation.
- Removable water tank system.
- 2mW line laser.
- Spirit level for easy field installation.
- Machine supplied without cable.
- Supplied with new ZERO DUST system already assembled. Also provided with a second anti-splash standard protector

Accessories:



Ref. 51916
Tile Fixer DV/DC/DCX/DS/DX



Ref. 51914
Roller Table Extension DU/DC/DCX/DS/DX (from 2013)



Ref.
Cables with plug

DS-250 N 1000	PREMIUM	40 3/16" 102 cm	28 3/8x28 3/8" 72x72 cm	2 1/16" 51 mm	1" 25 mm	1" 25.4 mm	10" 250 mm	66 15/16x33 7/8x50" 170x86x127 cm	201.7 Lb 91.5 kg	243 Lb 110 kg	1	**1		
DS-250 N 1300	PREMIUM	51 15/16" 132 cm	36 13/16x36 13/16" 93.5x93.5 cm	2 1/16" 51 mm	1" 25 mm	1" 25.4 mm	10" 250 mm	78x33 7/8x50" 200x86x127 cm	212.7 Lb 96.5 kg	265 Lb 120 kg	1	**1		
DS-250 N 1500	PREMIUM	59 13/16" 152 cm	42 5/16x42 5/16" 107.5x107.5 cm	2 1/16" 51 mm	1" 25 mm	1" 25.4 mm	10" 250 mm	86 5/8x33 7/8x50" 220x86x127 cm	220 Lb 100 kg	276 Lb 125 kg	1	**1		

Cutting capabilities may vary depending on the head position, special plates and disc diameter.

Ref. 52945 (3F): 4 CV/HP.

	REF	52920	52922	
DS-250 N 1000	Voltage	230V-50 Hz.	220V-60 Hz.	
	RPM	2800	3400	
DS-250 N 1300	REF	52930		
	Voltage	230V-50 Hz.		
	RPM	2800		
DS-250 N 1500	REF	52940	52942	52945
	Voltage	230V-50 Hz.	220V-60 Hz.	380V-50 Hz. 3F
	RPM	2800	3400	2800