



**Extremely durable and robust**

In response to the needs of our customers, we have made the CMM-11 device resistant to accidental impacts that can lead to unit damage. The elastomer material used in the housing protects the unit if it is dropped and absorbs the shocks caused by such impacts.



**Good visibility in any conditions**

Insufficient lighting where the measurements are being taken is not an obstacle anymore thanks to the integrated flashlight.



**Protection against dust penetration and streams of water**

The housing has been designed for use in the field. The IP65 degree provides protection the unit against dust penetration and accidental flooding with a stream of water.



**Compact housing**

Limited space in your tool box? It is not a problem with CMM-11. Thanks to the small dimensions, the unit even fits in your pocket.



**Wireless communication**

The device can wirelessly send the results of measurements ("live" mode) to the mobile application – Sone! Multimeter Mobile. It enables the recording and storage of results, notes and photos can be added or files attached to e-mail messages later on.

**Pocket multimeter with a strong character**

## Technical specification

Measurement functions	Range	Resolution	Accuracy ±(% m.v. + digits)
AC / DC voltage	to 600 V	0.001 V	±(1.0% m.v. + 3 digits)
AC / DC current	to 10.00 A	0.1 µA	±(1.0% m.v. + 3 digits)
Resistance	40.00 MΩ	0.1 Ω	±(1.0% m.v. + 4 digits)
Frequency	100.0 kHz	0,001 Hz	±(1.0% m.v. + 5 digits)
Capacity	4000 µF	0.01 nF	±(3.0% m.v. + 5 digits)
Operating cycle (%)	✓	0.1%	±(1.2% m.v. + 2 digits)
Continuity / Diode test	✓ / ✓		

  

Basic features	
Counting	4.000 digits
HOLD	✓
Manual / automatic range selection	✓ / ✓

  

Advanced features	
MIN / MAX	✓ / ✓
TRMS measurement	✓
Memory	in mobile application
Bluetooth communication	✓

  

Other features	
Easy access to A / mA fuses	✓ / ✓
Auto-off	✓
Empty battery indication	✓
Integrated flashlight	✓
Beeper	✓

  

Display	
Type	segment-based
Display backlight	✓

  

Safety and conditions for use	
Measuring category (EN 61010)	CAT III 600 V
Protection class	IP65
Dimensions	121 x 67 x 35 mm
Operating temperature	5...40°C
Storage temperature	-20...60°C

## Standard accessories



2x measuring cables  
WAPRZCMP1



2x LR03 AAA  
1,5 V battery



calibration  
certificate