

UT258 SERIES AC/DC Leakage Clamp Meters

UNI-T®

UT258A



EN61010-1
EN61010-2-032
EN61326-1



■ UT258A

SPECIFICATIONS



Specifications	Range	Best Accuracy
Model		UT258A
AC/DC Current (A)	0mA~60.0A	±(2%+5)
Resolution	1mA	
Frequency Response	45Hz~200Hz	
Features		
Display Mode	Four Digits LCD display	✓
Clamp Size	Φ7mm	✓
Auto Range		✓
RS-232 Interface		✓
Date Storage		99
Set to Zero Function	Adjust "ZERO" key to return to zero	✓
Date Hold		✓
Line Voltage	AC 600V	✓
Auto Power Off	5 Minutes	✓
Low Battery Indication	Around 7.2V	✓
Sampling Rate	2 Times/s	✓
Working Current	10mA	✓

GENERAL CHARACTERISTICS

Power Supply	9V Battery (6F22)
Product Color	Red and Grey
Product Net Weight	180g (Included Batteries)
Product Size	168mm×65mm×34mm
Standard Accessories	Batteries, Software CD, RS232 Interface Cable
Standard Individual Packing	Gift Box, English Manual, Toolbox
Standard Quantity Per Carton	20PCs
Standard Carton Measurement	375mm×315mm×220mm (0.026 CBM Per Standard Carton)
Standard Carton Gross Weight	10 Kg