

## 22" Full HD LED Monitor

VA2259-sh



The ViewSonic® VA2259-sh is a 22" (21.5" viewable) Full HD LED monitor with SuperClear® AH-IPS Panel technology, offering clearly sharp color representation and outstanding screen performance at wide viewing angles. It is modernized with a minimalistic, borderless design which provides exceptional viewing experience for home entertainment or office work. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving. Built in with HDMI and VGA inputs, promising more flexible and reliable connectivity. With a 3-year warranty, Energy Star and EPEAT Silver certification, the VA2259-sh definitely is a great long-term investment for home and office users.

### **Key Features:**

SuperClear IPS panel technology

Frameless design

Versatile connectivity

Full HD 1080p resolution

Superior color rendering and intuitive settings

### **Designed for:**

Business

Home

# 22" Full HD LED Monitor

**VA2259-sh**

## Specifications

<b>LCD PANEL</b>	Type	22" W (21.5" Viewable) AH-IPS Type
	Display Area	476.064mm x 267.786mm
	Resolution	Full HD 1920 x 1080
	Brightness	250 cd/m <sup>2</sup> (Typ)
	Contrast Ratio	1000:1 (Typ), 700:1 (Min)
	Dynamic Contrast Ratio	50,000,000:1
	Viewing Angles	178° / 178° (Typ)
	Response Time	GTG <sub>5</sub> : 5ms (Typ)
	Backlight	1 WLED light bar
	Backlight Life	30,000 Hrs (Min)
	Panel Surface	Anti-Glare type, Hard-coating (3H)
<b>INPUT SIGNAL</b>	Frequency	Fh=54~85.5KHz ; Fv=48~76Hz
	Sync	Separate Sync, Composite Sync, Sync on Green
<b>COMPATIBILITY</b>	PC	1920 x 1080 (Non-Interlaced)
	Mac®	1920 x 1080
<b>CONNECTOR</b>	Digital	HDMI x 1
	Analog	VGA x 1
	Audio Out	3.5 mm jack x 1
	Audio In	3.5 mm jack x 1
<b>POWER</b>	Power	3-pin plug (CEE22) x 1
	Voltage	AC 100-240V (Universal); 50/60Hz
	Consumption	22W ; Optimize:18W ; Conserve: 14W
<b>ERGONOMICS</b>	Tilt	22° ~ -5°
<b>WALL MOUNT</b>	VESA	100mm x 100mm
<b>OPERATING CONDITIONS</b>	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
<b>OPERATING CONDITIONS</b>	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
<b>DIMENSIONS</b>	Physical with stand	499.7 x 375.1 x 200mm
<b>WEIGHT</b>	Net with stand	2.84kg
<b>REGULATIONS</b>		CE EMC, CB, RoHS Green BOM & RoHS DoC, REACH SVHC List & DoC, ErP, WEEE, US NRTL w/ CA, FCC-B w/ ICES003, Energy Star , EPEAT Silver, Mexico-CoC, Mexico Energy, BSMI, PSB, RCM, MEPS, CCC, CEL Level 1, CECP
<b>WARRANTY</b>		*Warranty offered may differ from market to market
<b>PACKAGE CONTENTS</b>		LCD Display / Power Cable / VGA Cable / Quick Start Guide *Actual content may differ from market to market