

## Key Features

- HDMI and VGA Input
- SuperClear® IPS Technology for rich colors at wide angles
- 75Hz and Adaptive sync to eliminate screen tearing & reduce stuttering
- Eye-Care technology for comfortable viewing
- VESA wall mountable



## Product Description

The ViewSonic VA2418-sh is a 24" Full HD IPS monitor with HDMI and VGA input for business or home usage. With SuperClear® IPS technology and Full HD resolution, images are clear and detailed from a wide range of viewing angles. This monitor provides six ViewMode presets that deliver optimized screen performance in different applications. Even if used for gaming, users can move without screen tearing. Eye-Care technology and energy-saving Eco mode help to eliminate eyestrain from extended viewing periods. With VESA-compatible mount support, this monitor is easy to setup in any environment.



Visit Us • www.viewsonic.com

## datasheet\_VA2418-sh

		ERCONOMICS	
Display	24	ERGONOMICS	-5° / 22°
Display Size (in.):	24	Tilt (Forward/Back):	-5* / 22*
Viewable Area (in.):	23.8	WEIGHT (IMPERIAL)	7.0
Panel Type:	IPS Technology	Net (lbs):	7.9
Resolution:	1920 x 1080	Net Without Stand (lbs):	6.8
Resolution Type:	FHD	Gross (lbs):	10.1
Static Contrast Ratio:	1,000:1 (typ)	WEIGHT (METRIC)	
Dynamic Contrast Ratio:	50M:1	Net (kg):	3.6
Light Source:	LED	Net Without Stand (kg):	3.1
Brightness:	250 cd/m2 (typ)	Gross (kg):	4.6
Colors:	16.7M	DIMENSIONS (IMPERIAL) (W)	XHXD)
Color Space Support:	8 bit (6 bit + Hi-FRC)	Packaging (in.):	24.2 x 15.7 x 4.7
		Physical (in.):	21.6 x 15.9 x 8.6
Aspect Ratio:	16:9	Physical Without Stand (in.):	21.6 x 12.7 x 1.5
Response Time (Typical GTG):	5ms	DIMENSIONS (METRIC) (WXH	
Viewing Angles:	178º horizontal, 178º vertical	Packaging (mm):	615 x 398 x 119
Backlight Life (Hours):	30000 Hrs (Min)		
Curvature:	Flat	Physical (mm):	548 x 404 x 218
Refresh Rate (Hz):	Max. 75Hz (RGB Analog, HDMI (v1.4)) (Max)	Physical Without Stand (mm): GENERAL	548 x 322 x 38
Adaptive Sync:	Yes		cTUVus, FCC-B, ICES003, CEC, N
Blue Light Filter:	Yes	Regulations:	CoC, Mexico Energy, CE, CE EMC CB, RoHS, ErP, REACH, WEEE,
Flicker-Free:	Yes	Regulations:	EAC, UkrSEPRO, BSMI, KC, e-
1 IIGAGI-I ICC.			Standby
Color Gamut:	NTSC: 72% size (Typ), sRGB: 104% size (Typ)	PACKAGE CONTENTS:	VA2418-SH x1, 3-pin Mickey Mous Plug (IEC C5) x1, VGA Cable (Mal- Male) x1, Quick Start Guide x1
Pixel Size:	0.275 mm (H) x 0.275 mm (V)		Please dispose of in accordance w
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Recycle/Disposal:	local, state or federal laws.
COMPATIBILITY		Warranty:	*Warranty offered may differ from
PC Resolution (max):	1920x1080		market to market
Mac® Resolution (max):	1920x1080	Country Of Origin:	China
PC Operating System:	Windows 10 certified; macOS tested	Power Management:	Energy Star standards
Mac® Resolution (min):	1920x1080		
CONNECTOR			
VGA:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
Power in:	3-pin Mickey Mouse Socket (IEC C6)		
AUDIO			
POWER			
Eco Mode (Conserve):	19W		
Eco Mode (optimized):	22W		
Consumption (typical):	26W		
Consumption (max):	27W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.3W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	1, 2, Up, Down, Power		
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
VESA Compatible:	100 x 100 mm		
•			
Frequency Horizontal:	24 ~ 86KHz		
Frequency Vertical:	48 ~ 75Hz		
VIDEO INPUT			
Digital Sync:	TMDS - HDMI (v1.4)		
Analog Sync:	Separate - RGB Analog		

Copyright © ViewSonic Corporation 2000-2020. All rights reserved.

Separate - RGB Analog

Analog Sync: