

# ViewSonic® LED DISPLAY **VX2476-smhd**

## Key Features

- SuperClear® IPS technology
- Frameless bezel and metallic triangle stand
- Full HD 1080p resolution
- Flicker-Free and Blue Light Filter
- HDMI, DisplayPort and VGA input



## Product Description

The ViewSonic® VX2476-smhd is a 24" Full HD LCD monitor designed for both office and home use. With SuperClear® AH-IPS Panel technology, this monitor offers best-in-class screen performance with ultra-wide viewing angles. Vivid 1920x1080 resolution and dual speakers, combined with a sleek edge to edge frameless design, deliver an immersive viewing experience for home entertainment and multimedia applications. What's more, the minimalistic design of this monitor makes it perfect for nearly seamless multi-screen setups. HDMI, VGA, and DisplayPort inputs deliver flexible connectivity options for both computing and gaming environments, while ViewSonic's exclusive ViewMode feature provides intuitive presets for optimized screen performance in different applications. In addition, Flicker-Free technology, Blue Light Filter, and Low EMI help to minimize eye strain from extended viewing periods. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment for enterprise and home applications.

**Visit Us** - [www.viewsonic.com](http://www.viewsonic.com)

**LCD PANEL**

Size:	24" (16:9)
Panel Technology:	AH-IPS
Display Area:	23.8" (527.04x296.46mm)
Optimum Resolution:	1920x1080 (Full HD)
Brightness:	250 cd/m <sup>2</sup>
Contrast Ratio:	1,000 :1 (Typ.)
Dynamic Contrast Ratio:	80,000,000:1
Viewing Angle:	178° (H) / 178° (V)
Response Time:	4ms (GTGavg)
Backlight Life:	30,000 Hrs (Min.)
Color:	16.7 M
Panel Surface:	Anti-Glare type, Hard-coating (3H)

**INPUT SIGNAL**

Analog:	VGA
Digital:	HDMI / DisplayPort
Sync:	Separate Sync
Frequency:	24 ~82 kHz / 50 ~75 Hz

**COMPATIBILITY**

PC:	1920 x 1080
Mac:	1920 x 1080

**CONNECTOR**

Analog:	VGA x1
Digital:	HDMI x1 / DisplayPort x1
Audio in:	3.5mm jack x1
Audio Out:	3.5mm jack x1
Power:	External Power Adapter

**AUDIO**

Speaker:	3W x2
----------	-------

**POWER**

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	21 W ; Optimize: 18 W ; Conserve: 15 W
Save mode:	≤ 0.3 W

**ERGONOMICS**

Tilt:	17° ~ -5°
-------	-----------

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS**

Physical:	539.8 x 414.1 x 209 mm
-----------	------------------------

**WEIGHT**

Net:	2.97 Kg
------	---------

**REGULATIONS**

cULus, FCC-B, ICES-003, Energy Star 7.0, EPEAT Silver, NRCan, UL-MXCoC, Mexico Energy, CE, WEEE, EEL, BSMI, PSB, RCM, MEPS, SASO, VCCI, PSE, KC, e-Standby, CCC, China RoHS, CEL Level 1

**PACKAGE CONTENTS**

LCD Display / AC/DC Adapter / Power Cable / VGA Cable / HDMI Cable / Audio Cable