

ViewSonic® LED DISPLAY **VX3209-2K**

Key Features

- SuperClear® IPS technology
- Narrow bezel and T stand
- HDMI, DisplayPort and VGA inputs
- ViewMode technology
- Flicker-Free and Blue Light Filter



Product Description

The ViewSonic® VX3209-2K is a 32" (31.5" viewable) is a trendy QHD multimedia monitor with ultra slim bezel, narrow frame, and unique design stand featuring white for consumers to admire. In addition to carrying SuperClear® IPS-type panel technology and an upgrade 2560x1440 QHD resolution, users are able to see more content in detail, and appreciate sharper image quality with wider viewing angles. It is ideal for consumers who value resolution performance for video game or watching high quality video, providing the purest visual image quality available. With built in HDMI, DisplayPort, and VGA inputs, it is offer versatile connectivity options. With fast response time and color adjust function; users can enjoy enhanced gaming functions for casual gamers to conquer each battlefield while enjoying a more robust gaming experience. It also carries Flicker-Free and Blue light eye-care technology, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, ViewSonic's exclusive ViewMode™ function provides intuitive presets to deliver optimized screen performance for various applications.

Visit Us - www.viewsonic.com

LCD

Type:	32" (16:9)
Panel Technology:	IPS Technology
Display Area:	31.5" (698.112x392.688)
Optimum Resolution:	2560x1440 (QHD)
Brightness:	250 cd/m ² (Typ.)
Contrast Ratio:	1200 :1 (Typ.)
Dynamic Contrast Ratio:	80,000,000 :1
Viewing Angle:	178°(H) / 178° (V)
Response Time:	GTG:8ms(Typ.)
Panel Surface:	Anti-Glare type, Hard-coating (3H)
Light Source:	30000 Hrs (Min.)
Color Support:	1.07 Billion colors (8-bit+FRC)

INPUT

Analog:	VGA
Digital:	HDMI /DisplayPort
Frequency:	Separate Sync / Composite Sync / Sync on Green
Sync:	Fh = 30 ~ 82 kHz ; Fv = 50 ~ 75 Hz

COMPATIBILITY

PC:	2560x1440@60Hz
Mac:	2560x1440@60Hz

CONNECTOR

Analog:	VGA x1
Digital:	HDMI 1.4 x1 / DisplayPort 1.2a x1
Audio Out:	3.5mm jack x1
Power:	Internal Power Board

POWER

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	42W (Typ.) ; Optimize:32W ; Conserve:28W
Save mode:	≤0.5 W

ERGONOMICS

Tilt:	12° ~ -5°
-------	-----------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS

Physical (w/ stand):	720.5 (W) x 490.1 (H) x 188.13 (D) mm
----------------------	---------------------------------------

WEIGHT

Net (w/ stand):	6.23kg
-----------------	--------

REGULATIONS

CCC, China RoHS, CEL Level 1, BSMI

WALL MOUNT

100x100mm (screw SPEC, M5x10mm)

PACKAGE CONTENTS

LCD Display / Power Cable / HDMI Cable / Quick Start Guide
--