



LED DISPLAY

XG2703-GS

Key Features

- WQHD 1440p resolution
- SuperClear® IPS technology
- NVIDIA® G-SYNC™ technology
- NVIDIA Ultra Low Motion Blur(ULMB) technology
- Dark Boost



Product Description

The ViewSonic® XG2703-GS is the ideal display for gamers who require ultimate performance, rendering every frame your GPU can output in breathtaking detail. Featuring an incredible 165Hz refresh rate, as well as NVIDIA's G-Sync Technology, the XG2703-GS' variable refresh rate capabilities virtually eliminate screen tearing and stuttering for unbelievably fluid gameplay during fast-paced action sequences. Featuring cutting-edge display technology, this monitor boasts a 2560x1440 WQHD SuperClear® IPS panel for enhanced colour accuracy and greater viewing angles. A fast response time lets you seize control of the action, while low input lag provides smooth screen performance even in the most graphic-intense sequences. For a game-winning competitive edge, a Game Mode feature optimizes visuals for FPS, RTS and MOBA. On top of that, a Dark Boost function helps you target enemies lurking in the dark, while the monitor maintains brilliantly rich colors and contrast. With a gamer-inspired ergonomic stand that features an integrated headphone hook and cable management functionality, the XG2703-GS has all you need to conquer your gaming quests.

Visit Us www.viewsonic.com

LCD PANEL

Display Area:	596.74mm (H) x 335.66mm (V)
Resolution:	2560 x 1440
Brightness:	350 cd/m2
Contrast Ratio:	1000 : 1
Dynamic Contrast Ratio:	120M : 1
Viewing Angles:	178 degrees / 178 degrees
Response Time:	4ms (GtG) Under Ultra Fast Mode
Colour Gamut:	100% sRGB color coverage

INPUT SIGNAL

Frequency:	HDMI x Fh = 15 ~ 140KHz ; Fv = 24 ~ 138Hz DisplayPort x Fh = 34 ~ 209KHz ; Fv = 30 ~ 165Hz
------------	---

COMPATIBILITY

PC:	PC Compatible (up to 2560 x 1440)
Mac®:	Power Mac (up to 2560 x 1440)

CONNECTOR

Digital:	HDMI1.4 x 1 DisplayPort 1.2a x 1
Audio:	Earphone out x 1

SPEAKERS

2W x 2

USB

USB3.0 x 1 upstream USB3.0 x 2 downstream USB2.0 x 2 downstream

POWER

Power:	External DC connector
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	48W
Optimize:	40W
Conserve:	34W

ERGONOMICS

Tilt: 15~-5 degrees Swivel: 175/175 degrees Rotation: 90 degrees Height Adjust: 100mm
--

SPECIAL FEATURES

Flicker Free & Blue light filter

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D)

Physical with stand (mm/inch):	624.4mm x 532.4mm x 250.4mm
Physical without stand (mm/inch):	624.4mm x 383.6mm x 78.6mm
Packaging (mm/inch):	741mm x 481mm x 306mm

WEIGHT

Net with stand (kg/lbs):	7kg
Net without stand (kg/lbs):	4kg
Gross (kg/lbs):	9.5kg

REGULATIONS

cULus, FCC-B, ICES003, NRCan, MX-CoC, Mexico Energy, CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, CCC

PACKAGE CONTENTS

LCD Display AC/DC Adapter (1.8m) Power Cable (1.5m) DisplayPort Cable (1.5m) USB3.0 Cable (1.5m) Quick Start Guide
